

WALL LANTERN
Assembly Instructions
MODEL#:4180


CAUTION


- Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.
- Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.


TOOLS REQUIRED





Fixture


Fixture TOP


Mounting Unit


Mounting Screws


Wire Nuts



Cap Nuts

*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE

WALL LANTERN
Assembly Instructions
MODEL#:4180

STEP 1


Use the mounting screws to attach the mounting unit to the junction box




STEP 2

Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts. Secure with electrical tape


Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:	Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:
Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.	White Supply Wire or Insulated Wire (other than green) with silver conductor





step3


Place the canopy over the mounting unit and secure the fixture with
the cap nuts.



STEP 4

Install bulb(Not Included)

E26 TYPE A 60W



STEP 5

Put on the top cover and tighten the cap

