

For Professional Technical Support call **1-844-241-5521**

Where Used

In areas where water needs to be pumped away or transferred to another area. The 2-IN-1 Utility Pump is applicable for both of submersible and non-submersible circumstances. It can pump water down to 1/8 in. when using the included strainer for non-submersible transfer pump.


Typical Application

Submersible Application is suitable for draining or removing water from pits, sinks, window wells, basements, swimming pool covers, boats, low spot in yards, or other flooded area.

Non-submersible Application is suitable for draining or removing water from flooded area, clogged sinks, water beds, water basins, boats, stock tanks.

NOTICE: The 2-IN-1 utility pump should only be used with clear water.

Submersible Utility Pump Function



Non-Submersible Transfer Pump Function



Types of Utility Pumps

Portable utility pumps provide flexibility for use in various applications. Traditional utility pumps have 2 types based on their working conditions, submersible and non-submersible pumps. Submersible pumps must be submerged in water though non-submersible pumps can't be submerged in water. 2-IN-1 utility pump combines the 2 working conditions in one single pump and provides consumers more values and convenience than traditional utility pumps.

Frequently Asked Question

1. Is it water proof when use it as non-submersible pump?

Yes. It differs from traditional non-submersible pump. Its motor is also water-proof when use it as a non-submersible pump.

2. Is it using different voltage for submersible and non-submersible applications?

No. Both applications use same voltage 115V.

3. How to use the pump as submersible and non-submersible application?

Submersible application: submerge the pump in water and attach a garden hose to the pump outlet to discharge water to where you want.

Non-submersible application: attach the hose and strainer combination included to pump inlet, place the strainer in water, and attach a garden hose to pump outlet to discharge water to where you want. Fill water into pump through priming hole before operation.

4. Is the pump filled with oil?

No. It is an oil-free water-cooling pump.

5. Will the pump shut off automatically?

It is manual operation. You need to manually plug/unplug to start/stop the pump.

6. What additional items may I need?

A 5/8 in x 25 ft garden hose (Internet#100661323) or 5/8 in x 50 ft (Internet#100661312) is needed to attach for discharging.

7. Can the 2-IN-1 Utility pump be used as a sump pump or a pool pump?

No, this should not be used as a sump pump or pool pump. It is a portable utility pump.

8. What does priming the pump mean in the transfer mode, and is this important for the pump to work?

Yes, priming the pump is essential for the pump to operate in the transfer mode. Priming the pump removes all the air in the lines and prevents air lock. The suction hose and the pump must be completely filled and overflowing with water before the pump will operate.



Para comunicarse a Soporte técnico profesional llame al **1-844-241-5521**

Dónde se usan

En áreas donde se debe bombear el agua para sacarla o transferirla a otra área. La Bomba utilitaria 2 en 1 es adecuada tanto para utilizarla en modo sumergible como no sumergible.


Aplicaciones típicas

El modo sumergible es el adecuado para drenar o remover agua de pozos, fregaderos, pozos de ventanas, sótanos, cubiertas de piscinas, botes, partes bajas en jardines u otras áreas inundadas.

Su uso como bomba no sumergible sirve para drenar o remover agua de zonas inundadas, fregaderos atascados, lechos de agua, cuencas de agua, botes, tanques de almacenamiento.

NOTA: La bomba utilitaria 2 en 1 solo se debe utilizar con agua limpia.

Función de la bomba utilitaria sumergible



Función de la bomba de transferencia no sumergible



Tipos de bombas para servicios públicos

Las bombas utilitarias portátiles ofrecen flexibilidad para ser utilizadas en diferentes aplicaciones. Hay 2 tipos de bombas utilitarias tradicionales según las condiciones de funcionamiento: sumergibles o no sumergibles.

Las bombas sumergibles deben sumergirse en el agua pero las no sumergibles, no.

La bomba utilitaria 2 en 1 combina las 2 modalidades de funcionamiento en una sola bomba y ofrece a los clientes más valor y conveniencia que las bombas utilitarias tradicionales.

Preguntas frecuentes

1. ¿Es a prueba de agua si se la usa como una bomba no sumergible?

Sí. Es distinta a las bombas no sumergibles tradicionales. Su motor también es a prueba de agua cuando se la utiliza como una bomba no sumergible.

2. ¿Usa un voltaje diferente cuando se la sumerge y cuando no?

No. En ambos casos utiliza el mismo voltaje de 115V.

3. ¿¿ cómo usar la bomba como una aplicación sumergible y no sumergible?

Aplicación sumergible: sumerja la bomba en agua y conecte una manguera de jardín en la salida de la bomba para descargar el agua donde quiera.

Aplicación no sumergible: conecte la combinación de mangueras y filtros a la entrada de la bomba, introduzca el filtro en agua y conecte la mangueras de jardín a la salida de la bomba para descargar el agua donde quiera. Antes de la operación, inyecte agua en la bomba a través del agujero de inyección de combustible.

4. ¿La bomba contiene aceite?

No. Es una bomba refrigeradora de agua, sin aceite.

5. ¿La bomba se apaga automáticamente?

Es una bomba de operación manual. Debe enchufarla y desenchufarla manualmente para encender o apagar la bomba.

6. ¿Qué artículos adicionales podría necesitar?

Es necesario conectar una manguera de jardín de 15,8 mm x 7,62 m (Internet# 100661323) o de 15,8 mm x 15,24 m (Internet#100661312) para efectuar la descarga.

7. ¿Se puede utilizar la bomba utilitaria 2 en 1 como bomba de sumidero o bomba de piscina?

No, no se puede utilizar esta bomba como bomba de sumidero o bomba de piscina. Es una bomba utilitaria portátil.

8. ¿qué significa cargar la bomba con aceite en modo 1de transporte? Es importante para el trabajo de la bomba?

Sí, la bomba de llenado es esencial para que la bomba funcione en modo de transporte. Cargar la bomba elimina todo el aire de la línea y evita las cerraduras de aire. Antes de que la bomba funcione, la manguera de succión y la bomba deben estar completamente llenas de agua y desbordarse.

